

DOWNLIGHT CYGNUS Z2 930 74W 45° WHITE PREMIUM WHITE ON/OFF

Article number: N215-K0003-HE930-HA-H45-ZC03_950-S6-###





LED COB

Light colour 3000 [K] PREMIUM WHITE

CRI

90

 Led chip flux
 7822 [lm]

 Luminous flux
 6257 [lm]

 System power
 74 [W]

 Luminaire Efficiency
 85 [lm/W]

 Beam angle
 45°

 Controller
 45°

MacAdam ON/OFF

LUMINAIRE

 Weight
 2,8 [kg]

 Protection rating IP , IK , class
 IP 20, IK 3,

 Luminaire colour
 WHITE

 Cover
 Glass

 Operating voltage
 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.

+48 32 388 80 00



Generated: 19.05.2024



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska