

DOWNLIGHT

DOWNLIGHT CYGNUS Z2 827 20W 60° WHITE | ON/OFF

Article number: N215-K0003-RF827-H8-H60-ZC01_250-S6-###



COB

80

2700 [K] |

2694 [lm]

2155 [lm]


108 [lm/W]

ON/OFF

3 SDCM

20 [W]

60°





_					_
D	own	lia	ht	I F	D
-	•••••				-

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

 18	 	11	

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAIRE					
Weight	2,8 [kg]				
Protection rating IP , IK , class	IP 20, IK 3,				
Luminaire colour	WHITE				
Cover	Glass				
Operating voltage	220-240V 50-60Hz				

may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

Note: All data are typical values. Tolerance of measurements +/-10% System features

Generated: 19.05.2024