

## DOWNLIGHT

## DOWNLIGHT CYGNUS Z2 840 46W 60° WHITE | ON/OFF

Article number: N215-K0003-RF840-H8-H60-ZC02\_600-S6-###



COB

80

4000 [K] |

6814 [lm]

5451 [lm]


119 [lm/W]

ON/OFF

3 SDCM

46 [W]

60°





D	own	ligh	t L	ED
		· ·		

LED downlight for drop ceiling istallation. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Glass cover included. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 2x 37W

			-
			_
LU	MIN	IAIF	łΕ

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

UMINAINE				
Weight	2,8 [kg]			
Protection rating IP , IK , class	IP 20, IK 3,			
Luminaire colour	WHITE			
Cover	Glass			
Operating voltage	220-240V 50-60Hz			

may change with product improvements due to technical advances.

Note: All data are typical values. Tolerance of measurements +/-10% System features

## OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 19.05.2024