

DOWNLIGHT

DOWNLIGHT MAGNUM 850 25W 15° BLACK | ON/OFF

COB

80

5000 [K] |

3764 [lm]

3011 [lm]

120 [lm/W]

ON/OFF

3 SDCM

25 [W]

15°

Article number: N216-K0002-RF850-H8-O15-ZC02_650-##-###



Down		t L	ED
	· ·		

LED downlight for drop ceiling istallation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 24°, 36°, 60°. Maximum power is 37W.

11	I N	Л	M	Λ	IP	F

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	1,06 [kg]			
Protection rating IP , IK , class	IP 20, IK 3,			
Luminaire colour	BLACK			
Cover	Glass			
Operating voltage	220-240V 50-60Hz			

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 19.05.2024