

DOWNLIGHT

DOWNLIGHT MAGNUM 850 31W 24° BLACK | ON/OFF

Article number: N216-K0002-RF850-H8-O24-ZC03_800-##-###



UMINAIRE	
MacAdam	3 SDCM
Controller	ON/OFF
Beam angle	24°
Luminaire Efficiency	120 [lm/W]
System power	31 [W]
Luminous flux	3706 [lm]
Led chip flux	4633 [lm]
CRI	80
Light colour	5000 [K]
LED	COB

1,06 [kg]

BLACK

Glass

IP 20, IK 3,

220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 24°, 36°, 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Weight

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

+48 32 3

+48 32 388 80 00

www.cora.pl cora@cora.pl

 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 20.05.2024