

DOWNLIGHT

## DOWNLIGHT MAGNUM 930 21W 36° WHITE CRI97 ON/OFF

COR

IP 20, IK 3,

220-240V 50-60Hz

WHITE

Glass

Article number: N216-K0003-HI930-H8-O36-ZC02\_550-##-###



Light colour3000 [K] CRI97CRI90Led chip flux2402 [lm]Luminous flux1921 [lm]System power21 [W]Luminaire Efficiency91 [lm/W]Beam angle36°ControllerON/OFFMacAdam3 SDCMLUMINAIREWeight1,06 [kg]	LED	COB
Led chip flux2402 [lm]Luminous flux1921 [lm]System power21 [W]Luminaire Efficiency91 [lm/W]Beam angle36°ControllerON/OFFMacAdam3 SDCM	Light colour	3000 [K] CRI97
Luminous flux 1921 [lm]   System power 21 [W]   Luminaire Efficiency 91 [lm/W]   Beam angle 36°   Controller ON/OFF   MacAdam 3 SDCM	CRI	90
System power 21 [W]   Luminaire Efficiency 91 [Im/W]   Beam angle 36°   Controller ON/OFF   MacAdam 3 SDCM	Led chip flux	2402 [lm]
Luminaire Efficiency 91 [Im/W]   Beam angle 36°   Controller ON/OFF   MacAdam 3 SDCM	Luminous flux	1921 [lm]
Beam angle 36° Controller ON/OFF MacAdam 3 SDCM	System power	21 [W]
Controller ON/OFF MacAdam 3 SDCM	Luminaire Efficiency	91 [lm/W]
MacAdam 3 SDCM	Beam angle	36°
LUMINAIRE	Controller	ON/OFF
	MacAdam	3 SDCM
Weight 1,06 [kg]	LUMINAIRE	
	Weight	1,06 [kg]

## Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 24°, 36°, 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

**OPTIONS** 

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska