


DOWNLIGHT HEKTOR 2 MICRO 957 10W 18° GREY SPECIAL ON/OFF

Article number: N220-K0001-CC957-H7-I18-ZC01_250-A2-###





LED COB

Light colour 5700 [K] SPECIAL

CRI 9

Led chip flux 1318 [lm]

Luminous flux 1054 [lm]

System power 10 [W]

Luminaire Efficiency 105 [lm/W]

Beam angle 18°

Controller ON/OFF
MacAdam 3 SDCM

LUMINAIRE

Weight 0,4 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour GREY

Cover Plastic

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes.. Reflector beams available: 18°, 28° and 40°. Maximum power is 14W.

Note: All data are typical values. Tolerance of measurements $\pm 1.0\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 05.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska