



DOWNLIGHT HEKTOR 2 MICRO 940 14W 18° GREY PREMIUM WHITE ON/OFF

Article number: N220-K0001-PW940-HA-I18-ZC01_350-A2-###





LED COB

Light colour 4000 [K] PREMIUM WHITE

CRI

90 Led chip flux

Luminous flux

System power

Luminaire Efficiency

Beam angle

1887 [Im]

1509 [Im]

14 [W]

108 [Im/W]

Controller

MacAdam

18°

ON/OFF

3 SDCM

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes.. Reflector beams available: 18°, 28° and 40°. Maximum power is 14W.

LUMINAIRE

Weight 0,4 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour GREY

Cover Plastic

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 11.05.2024



+48 32 388 80 00





Street: Ignatza Hakuby 18 41-914 Bytom, Polska