


DOWNLIGHT HEKTOR 2 MICRO 935 11W 28° BLACK PREMIUM WHITE ON/OFF

Article number: N220-K0002-HE935-HA-I28-ZC01_250-A2-###





LED COB

Light colour 3500 [K] PREMIUM WHITE

CRI

90

 Led chip flux
 1545 [lm]

 Luminous flux
 1236 [lm]

 System power
 11 [W]

 Luminaire Efficiency
 112 [lm/W]

 Beam angle
 28°

Controller

MacAdam

3 SDCM

LUMINAIRE

Weight 0,4 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour BLACK
Cover Plastic
Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes.. Reflector beams available: 18°, 28° and 40°. Maximum power is 14W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 11.05.202



+48 32 388 80 00





Street: Ignatza Hakuby 18 41-914 Bytom, Polska