


DOWNLIGHT HEKTOR 2 MICRO 935 14W 28° BLACK PREMIUM WHITE ON/OFF

Article number: N220-K0002-HE935-HA-I28-ZC01_350-A2-###





LED COB

Light colour 3500 [K] PREMIUM WHITE

CRI

90

 Led chip flux
 2131 [lm]

 Luminous flux
 1704 [lm]

 System power
 14 [W]

 Luminaire Efficiency
 122 [lm/W]

 Beam angle
 122 [lm/W]

Controller

MacAdam

28°

ON/OFF

3 SDCM

LUMINAIRE

Weight 0,4 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour BLACK
Cover Plastic
Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes.. Reflector beams available: 18°, 28° and 40°. Maximum power is 14W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 09.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska