


DOWNLIGHT HEKTOR 2 MICRO 930 10W 28° BLACK CRI97 ON/OFF

Article number: N220-K0002-HI930-H7-I28-ZC01_250-A2-###





COB 3000 [K] CRI97 Light colour CRI Led chip flux 1144 [lm] Luminous flux 915 [lm] System power 10 [W] Luminaire Efficiency 92 [lm/W] Beam angle 28° Controller ON/OFF MacAdam 3 SDCM

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes.. Reflector beams available: 18°, 28° and 40°. Maximum power is 14W.

LUMINAIRE

Weight 0,4 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour BLACK

Cover Plastic

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 13.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska