


DOWNLIGHT HEKTOR 2 MICRO 940 11W 28° BLACK PREMIUM WHITE ON/OFF

Article number: N220-K0002-PW940-HA-I28-ZC01_250-A2-###





COB 4000 [K] PREMIUM WHITE Light colour

CRI

90 Led chip flux 1343 [lm] Luminous flux 1074 [lm] System power 11 [W] Luminaire Efficiency 98 [lm/W] Beam angle 28° Controller

ON/OFF MacAdam 3 SDCM

LUMINAIRE

Weight 0,4 [kg] Protection rating IP, IK, class IP 20, IK 3, BLACK Luminaire colour Cover Plastic Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes.. Reflector beams available: 18°, 28° and 40°. Maximum power is 14W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska