

DOWNLIGHT HEKTOR 2 MICRO 957 14W 40° WHITE SPECIAL ON/OFF

Article number: N220-K0003-CC957-H7-I40-ZC01_350-A2-###



COB

90

1820 [lm]

1456 [lm]

104 [lm/W]


ON/OFF

3 SDCM

14 [W]

40°

5700 [K] SPECIAL



Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes.. Reflector beams available: 18°, 28° and 40°. Maximum power is 14W.

LU	JM	INA	IRE

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	0,4 [kg]		
Protection rating IP , IK , class	IP 20, IK 3,		
Luminaire colour	WHITE		
Cover	Plastic		
Operating voltage	220-240V 50-60Hz		

may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

Note: All data are typical values. Tolerance of measurements +/-10% System features

Generated: 10.05.2024