

DOWNLIGHT HEKTOR 2 MICRO 930 14W 40° WHITE PREMIUM WHITE ON/OFF


Article number: N220-K0003-HE930-HA-I40-ZC01_350-A2-###



COB

90

3000 [K] PREMIUM WHITE



Down	lia	ht	
DOWIN	ny	ш.	ᄕ

LED downlight for drop ceiling istallation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes.. Reflector beams available: 18°, 28° and 40°. Maximum power is 14W.

	3 SDCM
MacAdam	ON/OFF
Controller	40°
Beam angle	
Luminaire Efficiency	118 [lm/W]
	14 [W]
System power	1651 [lm]
Luminous flux	2064 [lm]

LUMINAIRE

Light colour

Led chip flux

CRI

Weight	0,4 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska