

DOWNLIGHT HEKTOR 2 MICRO 835 10W 40° WHITE | ON/OFF

Article number: N220-K0003-RF835-H7-I40-ZC01_250-A2-###



COB

80

3500 [K] |

1391 [lm]

1112 [lm]


111 [lm/W]

ON/OFF

3 SDCM

10 [W]

40°



Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes.. Reflector beams available: 18°, 28° and 40°. Maximum power is 14W.

11	111	Л	N.	ΔI	R	F.

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAINE					
Weight	0,4 [kg]				
Protection rating IP , IK , class	IP 20, IK 3,				
Luminaire colour	WHITE				
Cover	Plastic				
Operating voltage	220-240V 50-60Hz				

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 10.05.2024