

## LINEAR LED LINE H 830 21W 576mm NANO OPAL BLACK | ON/OFF | THROUGH WIRING

Article number: H056-K0002-2F830-##-H2F-ZLN7\_500-###-3PO



3 SDCM



LED	SMD
Light colour	3000 [K] STANDARD
CRI	80
Led chip flux	3054 [lm]
Luminous flux	1801 [lm]
System power	21 [W]
Luminaire Efficiency	86 [lm/W]
Beam angle	NANO OPAL
Controller	ON/OFF

## **Linear LED**

Linear LED luminaire with through wiring connecting system . Available in white, black and grey. Any RAL palette colour available on enquiry. Aluminium housing. Suspended or surface installation possible. Diffusers: nano opal, micro-prismatic, low UGR

## **LUMINAIRE**

MacAdam

Weight 3,9 [kg] Protection rating IP, IK, class IP 20, IK 1, Luminaire colour BLACK Cover Plastic Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements  $\pm$ 1-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, wood pattern on inquiry, Tunable white on inquiry, Casambi on inquiry, DALI on inquiry,





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska