


## LINEAR LED LINE H 830 27W 1136mm LOW UGR GREY | ON/OFF |

Article number: H112-K0001-4F830-##-H4L-ZLN6\_350-###-###





LED SMD

Light colour 3000 [K] STANDARD

80

Led chip flux 3276 [lm] 1506 [lm] Luminous flux System power 27 [W] Luminaire Efficiency 56 [lm/W] LOW UGR Beam angle Controller ON/OFF

MacAdam 3 SDCM

LUMINAIRE

Weight 3,9 [kg] Protection rating IP, IK, class IP 20, IK 1, Luminaire colour BLACK Cover Plastic Operating voltage 220-240V 50-60Hz

**OPTIONS** 

## **Linear LED**

Linear LED luminaire. Available in white, black and grey. Any RAL palette colour available on enquiry. Aluminium housing. Suspended or surface installation possible. Diffusers: nano opal, micro-prismatic, low UGR

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

RAL colours on inquiry, wood pattern on inquiry, Tunable white on inquiry, Casambi on inquiry, DALI on inquiry,





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska