


LINEAR LED LINE H 930 38W 1136mm NANO OPAL BLACK | ON/OFF |

Article number: H112-K0002-4F930-##-H4F-ZLN6_500-###-###





LED SMD

Light colour 3000 [K] STANDARD

CRI 90

 Led chip flux
 5160 [lm]

 Luminous flux
 3096 [lm]

 System power
 38 [W]

 Luminaire Efficiency
 81 [lm/W]

 Beam angle
 NANO OPAL

 Controller
 ON/OFF

MacAdam 3 SDCM

LUMINAIRE

Weight 3,9 [kg]
Protection rating IP, IK, class IP 20, IK 1,
Luminaire colour BLACK
Cover Plastic

Operating voltage 220-240V 50-60Hz

Linear LED

Linear LED luminaire. Available in white, black and grey. Any RAL palette colour available on enquiry. Aluminium housing. Suspended or surface installation possible. Diffusers: nano opal, micro-prismatic, low UGR

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, wood pattern on inquiry, Tunable white on inquiry, Casambi on inquiry, DALI on inquiry,



Generated: 01.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska