

LINEAR

LINEAR LED LINE H 935 61W 2816mm LOW UGR GREY | ON/OFF |

Article number: H280-K0001-0F935-##-H0L-ZLN8_350-###-###





IMINAIRE	
MacAdam	3 SDCM
Controller	ON/OFF
Beam angle	LOW UGR
Luminaire Efficiency	65 [lm/W]
System power	61 [W]
Luminous flux	3974 [lm]
Led chip flux	8640 [lm]
CRI	90
Light colour	3500 [K] STANDARD
LED	SMD

Linear LED

Linear LED luminaire. Available in white, black and grey. Any RAL palette colour available on enquiry. Aluminium housing. Suspended or surface installation possible. Diffusers: nano opal, micro-prismatic, low UGR

LUMINAIRE

Weight	3,9 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	GREY
Cover	Plastic
Operating voltage	220-240V 50-60Hz

OPTIONS

RAL colours on inquiry, wood pattern on inquiry, Tunable white on inquiry, Casambi on inquiry, DALI on inquiry,



+48 32 388 80 00





Street: Ignatza Hakuby 18 41-914 Bytom, Polska

Note: All data are typical values. Tolerance of measurements +/-10% System features

may change with product improvements due to technical advances.