

LINEAR

LINEAR LED LINE M LENS 940 44W 1976mm LENS SYMETRIC (BATWING) WHITE | ON/OFF |

Article number: L196-K0003-7F940-##-BBW-ZLN8_350-###-###



SMD

90

6552 [lm] 6224 [lm]

44 [W]


141 [lm/W] LENS SYMETRIC (

BATWING)

ON/OFF

3 SDCM

4000 [K] STANDARD



Linear LED

Linear LED luminaire. Available in white, black and grey. Any RAL palette colour available on enquiry. Aluminium housing. Suspended or surface installation possible. Diffusers: nano opal, micro-prismatic, low UGR

 ΜΙΝ	 DE

LED

CRI

Light colour

Led chip flux

Luminous flux System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

Weight	3,9 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, wood pattern on inquiry, Tunable white on inquiry, Casambi on inquiry, DALI on inquiry,





S

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska