

## LINEAR

## LINEAR LED LINE M LENS 830 71W 2256mm LENS 30° BLACK | ON/OFF |

Article number: L224-K0002-8F830-##-B30-ZLN5\_500-###-###




SMD

80

12216 [lm]

3000 [K] STANDARD

220-240V 50-60Hz



## Linear LED

Linear LED luminaire. Available in white, black and grey. Any RAL palette colour available on enquiry. Aluminium housing. Suspended or surface installation possible. Diffusers: nano opal, micro-prismatic, low UGR

| Luminous flux                                      | 11605 [lm]                       |            |        |
|--|----------------------------------|------------|--------|
| System power<br>Luminaire Efficiency<br>Beam angle | 71 [W]<br>163 [lm/W]<br>LENS 30° |            |        |
|  |                                  | Controller | ON/OFF |
|  |                                  | MacAdam    | 3 SDCM |
|  |                                  |            |        |
| LUMINAIRE  |                                  |            |        |
| Weight   | 3,9 [kg]                         |            |        |
| Protection rating IP , IK , class                  | IP 20, IK 1,                     |            |        |
| Luminaire colour                                   | WHITE                            |            |        |
| Cover  | Plastic                          |            |        |

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Operating voltage

LED

CRI

Light colour

Led chip flux

RAL colours on inquiry, wood pattern on inquiry, Tunable white on inquiry, Casambi on inquiry, DALI on inquiry,





+48 32 388 80 00





Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 17.09.2024