

LINEAR LED LINE M LENS 840 71W 2256mm LENS SYMETRIC (BATWING) WHITE | ON/OFF |

Article number: L224-K0003-8F840-##-BBW-ZLN5_500-###-###



LED	SMD
Light colour	4000 [K] STANDARD
CRI	80
Led chip flux	12744 [lm]
Luminous flux	12106 [lm]
System power	71 [W]
Luminaire Efficiency	171 [lm/W]
Beam angle	LENS SYMETRIC (BATWING)
Controller	ON/OFF
MacAdam	3 SDCM

Linear LED

Linear LED luminaire. Available in white, black and grey. Any RAL palette colour available on enquiry. Aluminium housing. Suspended or surface installation possible. Diffusers: nano opal, micro-prismatic, low UGR

LUMINAIRE

Weight	3,9 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	Plastic
Cover	220-240V 50-60Hz
Operating voltage	

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, wood pattern on inquiry, Tunable white on inquiry, Casambi on inquiry, DALI on inquiry,



Generated: 17.09.2024



+48 32 388 80 00



www.cora.pl
cora@cora.pl



Street: Ignatza Hakuby 18
41-914 Bytom, Polska