

LINEAR

LINEAR LED LINE M LENS 930 88W 2816mm LENS ASYMETRIC WHITE | ON/OFF |

Article number: L280-K0003-0F930-##-BAS-ZLN5_500-###-###




SMD

90

12900 [lm]

12255 [lm]

3000 [K] STANDARD



Linear LED

Linear LED luminaire. Available in white, black and grey. Any RAL palette colour available on enquiry. Aluminium housing. Suspended or surface installation possible. Diffusers: nano opal, micro-prismatic, low UGR

LUMINAIRE	3.9 [ka]
MacAdam	3 SDCM
Controller	ON/OFF
Beam angle	LENS ASYMETRIC
Luminaire Efficiency	139 [lm/W]
System power	88 [W]

 Weight
 3,9 [kg]

 Protection rating IP , IK , class
 IP 20, IK 1,

 Luminaire colour
 Plastic

 Cover
 220-240V 50-60Hz

 Operating voltage
 Vertice

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

LED

CRI

Light colour

Led chip flux

Luminous flux

RAL colours on inquiry, wood pattern on inquiry, Tunable white on inquiry, Casambi on inquiry, DALI on inquiry,



+48 32 388 80 00



Ő

Street: Ignatza Hakuby 18 41-914 Bytom, Polska

