


LINEAR LED LINE M 830 46W 1416mm MICROPRYZMA WHITE | ON/OFF |

Article number: M140-K0003-5F830-##-C5M-ZLN6_500-###-###





.ED SMD

Light colour 3000 [K] STANDARD

CRI 8

 Led chip flux
 7635 [lm]

 Luminous flux
 4504 [lm]

 System power
 46 [W]

 Luminaire Efficiency
 98 [lm/W]

Beam angle MICROPRYZMA

Controller ON/OFF
MacAdam 3 SDCM

LUMINAIRE

Weight 3,9 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz

Linear LED

Linear LED luminaire. Available in white, black and grey. Any RAL palette colour available on enquiry. Aluminium housing. Suspended or surface installation possible. Diffusers: nano opal, micro-prismatic, low UGR

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, wood pattern on inquiry, Tunable white on inquiry, Casambi on inquiry, DALI on inquiry,



Generated: 14.08.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska