


LINEAR LED LINE M 930 54W 1696mm OPAL BLACK | ON/OFF |

Article number: M168-K0002-6F930-##-C6O-ZLN6_500-###-###



.ED SMD

Light colour 3000 [K] STANDARD

CRI

 Led chip flux
 7740 [lm]

 Luminous flux
 3870 [lm]

 System power
 54 [W]

 Luminaire Efficiency
 72 [lm/W]

 Beam angle
 OPAL

 Controller
 ON/OFF

 MacAdam
 3 SDCM

LUMINAIRE

 Weight
 3,9 [kg]

 Protection rating IP , IK , class
 IP 20, IK 1,

 Luminaire colour
 BLACK

 Cover
 Plastic

 Operating voltage
 220-240V 50-60Hz

Linear LED

Linear LED luminaire. Available in white, black and grey. Any RAL palette colour available on enquiry. Aluminium housing. Suspended or surface installation possible. Diffusers: nano opal, micro-prismatic, low UGR

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, wood pattern on inquiry, Tunable white on inquiry, Casambi on inquiry, DALI on inquiry,



Generated: 16.07.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska