


# LINEAR LED LINE M 935 54W 1696mm MICROPRYZMA WHITE | ON/OFF |

Article number: M168-K0003-6F935-##-C6M-ZLN6\_500-###-###



LED	SMD
Light colour	3500 [K] STANDARD
CRI	90
Led chip flux	8010 [lm]
Luminous flux	4806 [lm]
System power	54 [W]
Luminaire Efficiency	89 [lm/W]
Beam angle	MICROPRYZMA
Controller	ON/OFF
MacAdam	3 SDCM

## Linear LED

Linear LED luminaire. Available in white, black and grey. Any RAL palette colour available on enquiry. Aluminium housing. Suspended or surface installation possible. Diffusers: nano opal, micro-prismatic, low UGR

## LUMINAIRE

Weight	3,9 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	Plastic
Cover	220-240V 50-60Hz
Operating voltage	

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## OPTIONS

RAL colours on inquiry, wood pattern on inquiry, Tunable white on inquiry, Casambi on inquiry, DALI on inquiry,



Generated: 17.09.2024



+48 32 388 80 00



www.cora.pl  
cora@cora.pl



Street: Ignatza Hakuby 18  
41-914 Bytom, Polska