


LINEAR LED LINE M 840 44W 1976mm MICROPRYZMA GREY | ON/OFF |

Article number: M196-K0001-7F840-##-C7M-ZLN8_350-###-###



.ED SMD

Light colour 4000 [K] STANDARD

CRI 8

 Led chip flux
 6840 [lm]

 Luminous flux
 4104 [lm]

 System power
 44 [W]

 Luminaire Efficiency
 93 [lm/W]

Beam angle MICROPRYZMA

Controller ON/OFF
MacAdam 3 SDCM

LUMINAIRE

 Weight
 3,9 [kg]

 Protection rating IP , IK , class
 IP 20, IK 1,

 Luminaire colour
 GREY

 Cover
 Plastic

 Operating voltage
 220-240V 50-60Hz

Linear LED

Linear LED luminaire. Available in white, black and grey. Any RAL palette colour available on enquiry. Aluminium housing. Suspended or surface installation possible. Diffusers: nano opal, micro-prismatic, low UGR

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, wood pattern on inquiry, Tunable white on inquiry, Casambi on inquiry, DALI on inquiry,



Generated: 14.08.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska