


## LINEAR LED LINE M 930 88W 2816mm NANO OPAL GREY | ON/OFF |

Article number: M280-K0001-0F930-##-C0F-ZLN5\_500-###-###



\_ED SMD

Light colour 3000 [K] STANDARD

CRI 9

Led chip flux 12900 [lm]

Luminous flux 7740 [lm]

System power 88 [W]

Luminaire Efficiency 88 [lm/W]

Beam angle NANO OPAL

Controller ON/OFF

MacAdam 3 SDCM

## **Linear LED**

Linear LED luminaire. Available in white, black and grey. Any RAL palette colour available on enquiry. Aluminium housing. Suspended or surface installation possible. Diffusers: nano opal, micro-prismatic, low UGR

## LUMINAIRE

Weight 3,9 [kg]
Protection rating IP , IK , class IP 20, IK 1,
Luminaire colour BLACK
Cover Plastic
Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, wood pattern on inquiry, Tunable white on inquiry, Casambi on inquiry, DALI on inquiry,



Generated: 17.09.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska