


LINEAR LED LINE M 830 61W 2816mm NANO OPAL WHITE | ON/OFF |

Article number: M280-K0003-0F830-##-C0F-ZLN8_350-###-###



SMD

3000 [K] STANDARD Light colour

CRI

Led chip flux 9828 [lm] Luminous flux 5798 [lm] System power 61 [W] 95 [lm/W] Luminaire Efficiency NANO OPAL Beam angle Controller ON/OFF

LUMINAIRE

MacAdam

Weight 3,9 [kg] Protection rating IP , IK , class IP 20, IK 1, Luminaire colour Plastic

220-240V 50-60Hz Cover

Operating voltage

3 SDCM

OPTIONS

RAL colours on inquiry, wood pattern on inquiry, Tunable white on inquiry, Casambi on inquiry, DALI on inquiry,

(€ EM 2K

Linear LED

Linear LED luminaire. Available in white, black and grey. Any RAL palette colour available on enquiry. Aluminium housing. Suspended or surface installation possible. Diffusers: nano opal, micro-prismatic, low UGR

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska